# Wax Rings

**Product Specifications** 



ML11581

# **Description**

Mainline wax rings fit 3" and 4" waste lines. They extend short horn bowls and will not harden or deteriorate. They form a gas-tight, odor-tight and water-tight seal.

## **Directions for Use**

- Be sure the wax ring is at room temperature (about 70°F). If wax ring is too cold a good seal may not be a made or the toilet bowl could crack while making the installation.
- With the toilet bowl upside down on a protective pad or blanket, place the wax ring around the discharge opening. Press firmly to assure adhesion when the toilet is inverted.
- Using Mainline Stay Soft Putty make a putty ring about 1 inch high around the outside rim of the toilet. This will make a seal between the toilet rim and the floor.
- Carefully set toilet down on bolts and twist bowl slightly to spread wax and putty to make a tight seal. Tighten bolts carefully to prevent breaking the bowl.

### **BOWLWAX RINGS**

✓ To Submit	Part No.	Description
	ML11580	3" or 4" Wax Ring
	ML11581	3" or 4" Reinforced Wax Ring (Wall or Floor)
	ML11582	3" or 4" Deep Wax Ring
	ML11583	3" or 4" Wax Ring with Flange
	ML11584	4" Wax Ring with Flange
	ML11585	3" or 4" Reinforced Wax Ring with Flange
	ML11586	3" or 4" Deep Wax Ring with Flange

### **BOWLWAX RINGS WITH BOLTS**

✓ To Submit	Part No.	Description
	ML11587	3" or 4" Wax Ring with 1/4" X 2-1/4" Brass Bolts
	ML11588	3" or 4" Wax Ring with Flange 1/4" X 2-1/4" Brass Bolts
	ML11589	4" Wax Ring with Flange 1/4" x 2-1/2" Brass Bolts
	ML11590	3" or 4" Deep Wax Ring with Flange 1/4" X 3-1/2" Brass Bolts

### **URINAL WAX RINGS**

✓ To Submit	Part No.	Description
	ML11591	2" Reinforced Urinal Wax Ring

# ML11582 ML11583 ML11584 ML11585 ML11586 ML11587 ML11588 ML11589 ML11590 ML11591

ML11580

### **MSDS**

See MSDS sheet for more details.

### Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.