Well Tanks, In-Line - Tan

Product Specifications



PRODUCT FEATURES

- Stainless Steel System Connection
- Heavy Duty Butyl Diaphragm
- Polypropylene Tank Liner
- Projection Welded Air Valve
- Water Inlet Agitator
- 5 Year Warranty



✓ To Submit	Part No.	Description	Size
	MLWI2-T	In-Line Well Tank, Tan	2.0 gallon
	MLWI4-T	In-Line Well Tank, Tan	4.4 gallon
	MLWI8-T	In-Line Well Tank, Tan	7.6 gallon
	MLWI14-T	In-Line Well Tank, Tan	14.0 gallon



Warranty: See warranty information for more details.

All dimensions listed are nominal. MAINLINE[®] reserves the right to make product and material changes at any time without notice.

Contact your sales representative for more information or visit our website at mainlinecollection.com

Well Tanks, In-Line - Tan

Product Specifications

Part Lit Gal A		Max Accept	Accept Height		B Diameter		Sys Conn. (NPTM)	Factory Working Pre-charge Pressure		Ship Wt.		
			Factor	Mm	Ins	Mm	Ins	Ins	PSIG	PSIG	Kg	lbs
MLW12-T	8	2.0	0.45	330	13	203	8	3/4	38	125	2.0	5
MLW14-T	17	4.4	0.55	381	15	279	11	3/4	38	125	4.0	9
MLW18-T	29	7.6	0.43	559	22	279	11	3/4	38	125	7.0	15
MLW114-T	53	14.0	0.81	559	22	381	15	1	38	125	10.0	22

All dimensions and weights are approximate

SPECIFICATIONS

Description	Shell	Diaphragm	Liner	Coating
Diaphragm Construction	Deep Drawn Steel	Heavy Duty Butyl	Polypropylene	2-Part Urethane

MAX OPERATING CONDITIONS

Operating	Working
Temperature	Pressure
200°F (93°C)	125 PSIG (861.8kPa)



Complies with Low Lead Plumbing Law

Warranty: See warranty information for more details.

All dimensions listed are nominal. MAINLINE[®] reserves the right to make product and material changes at any time without notice.

Contact your sales representative for more information or visit our website at mainlinecollection.com