Lead Free* Brass Swing Check Valve, Threaded

Product Specifications

MAINLINE

✓ To Submit	Part #	Size		
	ML246AB-1/2	1/2"		
	ML246AB-3/4	3/4"		
	ML246AB-1	1"		
	ML246AB-11/4	1-1/4"		
	ML246AB-11/2	1-1/2"		
	ML246AB-2	2"		

Product Features:

- 200# WOG
- Forge Brass Body
- Low Lead Brass Disc
- Virgin PTFE Gasket
- Threaded Ends
- Horizontal "T" Pattern
- AB1953, NSF-61 & NSF-372 Certified




Materials & Specifications:

Item	Description	Material	Specification
1	Cap	Low Lead Brass	C28500
2	Gasket	PTFE	PTFE
3	Pin	Low Lead Brass	C28500
3	Screw	Brass	-
4	Disc	Low Lead Brass	C28500
5	Body	Low Lead Brass	C28500

Dimensions (inches), Weights (lbs.), & Valve Data:

Size	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"
Н	1.41	1.46	1.78	2.05	2.3	2.78	3.2	3.45	4.18
L	2.07	2.38	2.84	3.23	3.74	4.21	5.6	6.05	7
Wt	1.13	1.32	1.62	2.14	2.55	3.35	4.9	7.75	11.65



Pressure/Temperature Ratings 200# WOG 450°F Max Temp

Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.



