



MLP72333

The Pump Authority.

THERMOPLASTIC

Pedestal Sump Pump

1/3
HORSEPOWER
MOTOR

FEATURES

- Energy efficient 1/3 HP split capacitor motor. Lower amp draw, runs cooler, lasts longer
- Reinforced thermoplastic pump base and housing for durability
- Open type, air cooled motor
- Non-clogging stainless steel impeller for ultimate durability and corrosion resistance
- 1-1/4" NPT discharge
- Handles up to 3/8" solids
- Automatic operation with vertical style float switch
- Chemical resistant polyethylene float ball
- Motor is thermally protected with automatic reset thermal protector
- Solid plated steel drive shaft will not crack or break
- Durable lower bronze bushing
- Upper and lower motor ball bearings are permanently lubricated
- Stainless steel fasteners
- Every unit is 100% quality tested

ENERGY EFFICIENT
SPLIT CAPACITOR MOTOR

3 YEAR
LIMITED WARRANTY




MainlineCollection.com

SUBMERSIBLE

THERMOPLASTIC

Pedestal Sump Pump

1/3
HORSEPOWER
MOTOR



| Application | |
|--|---------------------------------------|
| Pedestal sump pump for typical residential and commercial applications | |
| Motor Specifications | |
| Horsepower | 1/3 HP |
| Voltage | 120 |
| Amps | 2.76 |
| Hertz | 60 Hz |
| Phase | Single |
| RPM | 1800 RPM |
| Motor Type | Permanent Split Capacitor (PSC) |
| Insulation | Class A |
| Circuit Requirements | 15 amp (min) individual circuit |
| Duty Rating | Continuous |
| Upper Motor Bearing | Ball Bearing |
| Lower Motor Bearing | Ball Bearing |
| Cooling | Air cooled |
| Motor Protection | Auto reset thermal overload protector |
| Pump Specifications | |
| Discharge Size | 1-1/4" NPT |
| Cord Length | 10' |
| Cord Type | SJTW, UL listed, 3-wire, 18 gauge |
| Pump Housing | Reinforced Thermoplastic |
| Pump Base | Reinforced Thermoplastic |
| Column Material | Reinforced Thermoplastic |
| Drive Shaft | Solid plated steel |
| Drive Shaft Bearing | Bronze bushing |
| Impeller Material | Stainless steel |
| Impeller Type | Non-clogging |
| Float Rod | Galvanized steel |
| Float Rod Guide | Thermoplastic |
| Float Ball | Polyethylene |
| Solids Handling | 3/8" spherical |
| Liquid Temp. Range | 32°- 120° F |
| Operation | Automatic or non-automatic |
| Fasteners | Stainless steel |
| Max Flow Rate | 50 Gallons per minute |
| Maximum Head | 20 feet |
| Max Pressure | 8.7 psi |
| Weight | 14.2 lbs |
| Automatic Switch Specifications | |
| Type | Vertical |
| Switch on point | Adjustable |
| Switch off point | 4" |

