




Gas Connector W/VLV Uncoated

Product Specifications

Product Features

- 1/2OD 1/2FIP x 1/2MIP
- Tubing..... Annealed, 304 stainless steel (ASTM A240)
- Flare nuts..... Brass or plated steel
- Adapters..... Brass or plated steel
- Meets SAE J512 standard – 45° flare (with the exception of 15/16" – 16 threads of 5/8"OD)
- Approved for indoor and outdoor use
- Temperature rating with adapters: -40°F to 150°F
- Temperature rating with valves: -40°F to 125°F
- 100% Factory leak tested
- When installing a new appliance or when an existing appliance is moved to a new location a NEW gas connector must be used per manufacturer's installation instructions and per product standards ANSI Z21.24/CSA 6.10 and ANSI Z21.75/CSA 6.27.
- Avoid repeated bending, flexing, or extreme vibration. Do not use
- on portable gas generators due to excessive vibration.



Indoor

- Range
- Dryer
- Water Heater
- Gas Fireplace
- Garage Heater
- Wall Heater
- Tankless Water Heater
- Furnace
- Space Heaters

Outdoor

- Rooftop Units
- Outdoor Dryer
- Stationary Outdoor Grills
- Gas Fire Pits

Manufactured Home

- Mobile Home Gas Meter
- Cross-over Gas Connection Kits

Design Certifications and Approvals

- ANSI Z21.24/CSA 6.10 – Connectors for Gas Appliances
- ANSI Z21.75/CSA 6.27 – Connectors for Outdoor Appliances and Manufactured Homes
- City of New York – MEA #376-92-M
- Approved by the Commonwealth of Massachusetts Board of State Examiners of Plumbers and Gas Fitters – connector length may not exceed 36".

⚠ WARNING

All installations must completely comply with all manufacturing company warnings and instructions, national, state and local codes and all applicable ANSI standards.

Connector Minimum Flow Capacity – **For Natural Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 0.64 SG., 1000 BTU per Cu. Ft. at 0.5 inch Water Column (124 Pa) Pressure Drop

Nominal OD (in)	Nominal ID (in)	12"	18"	24"	36"	48"
1/2"	3/8"	102,000	93,100	85,000	71,100	60,500

Connector Minimum Flow Capacity – **For Propane Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 1.55 SG., 2500 BTU per Cu. Ft. at 0.5 inch Water Column (124 Pa) Pressure Drop

Nominal OD (in)	Nominal ID (in)	12"	18"	24"	36"	48"
1/2"	3/8"	163,200	148,960	136,000	113,760	96,800

NOTICE: When using 0.2 water column pressure drop, capacity can be determined by multiplying the values above by 0.632 (for both natural and propane gas).

✓ To Submit	Part Number	Description
	ML10683	12"
	ML10684	18"
	ML10685	24"
	ML10686	36"
	ML10687	48"



Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.

Contact your sales representative for more information or visit our website at mainlinecollection.com