# PerfectSteam Generator

# LUXART.

### **Product Specifications**



#### **SPECIFICATIONS**

Input Voltage	208-240VAC	Single	Phase
Kilowatt Rating			10.0
Maximum Amperage		46	AMPS
Water Inlet		3/8	" NPT
Steam Outlet		1/2	" NPT
Electrical connection		Har	d-wired
Maximum Room Size (cu	ubic Feet)		240

The steam generator shall approximately be 17.5"  $\times$  8"  $\times$  9.5" in dimension. The generator tank shall be made from stainless steel the controller 5.5"  $\times$  3.4"  $\times$  34", and the steam head 2.5"Dia  $\times$  2".

#### **FEATURES**

- Requires LXTTC-OSS Steam Control. Available in four finishes
- Simple Sized no complicated formulas
- Constant steam at a constant rate (no steam lags or bursts)
- 1 year in home, five year "no questions asked" factory warranty
- Can be plumbed 50 feet from the shower enclosure without having to purchase a larger kW unit
- Time, temperature, memory, and clock control; all metal construction – not plated plastic

## **Shipping Information:**

Weight21	lbs.
Length20	in.
Width7	in.
Height11	in.

#### **INSTALLATION NOTES**

Install this generator according to the supplied installation guide. Follow local plumbing and electrical codes. Unit must be accessible.

Generator is factory sized: L x W x H = Cubic Feet. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

