

ABS CONSTRUCTION

# Rubber Boot Check Valves

## MAIN FEATURES

- 1-1/2" ABS check valve with 1-1/2" rubber boots
- Weighted flapper valve
- Stainless steel hose clamps
- Full flow design
- Rubber boots dampen water hammer
- Easy to install
- Vertical or horizontal installation
- Rated for 4.3psi (10' of head)
- Maximum temperature 140°F

**1 YEAR**  
LIMITED WARRANTY



**MLP79522**

## MAIN FEATURES

- 1-1/2" ABS check valve with 1-1/2" x 1-1/4" rubber boots
- For use with 1-1/4" and/or 1-1/2" pipe
- Weighted flapper valve
- Stainless steel hose clamps
- Full flow design
- Rubber boots dampen water hammer
- Easy to install
- Vertical or horizontal installation
- Rated for 4.3psi (10' of head)
- Maximum temperature 140°F

**1 YEAR**  
LIMITED WARRANTY



**MLP79502**

## MAIN FEATURES

- 2" ABS check valve with 2" rubber boots
- Weighted flapper valve
- Stainless steel hose clamps
- Full flow design
- Rubber boots dampen water hammer
- Easy to install
- Vertical or horizontal installation
- Rated for 4.3psi (10' of head)
- Maximum temperature 140°F

**1 YEAR**  
LIMITED WARRANTY



**MLP79529**