

Ball Valve / Check Valve / Union Combination

PVC

TYPE 1

FEATURES

- Constructed from durable Type 1 PVC
- Weighted Buna-N flapper seal and angle seat design for low pressure seal
- Full flow design reduces flow loss
- True union design for easy installation, servicing & cleaning
- Socket end connections
- Can be installed vertically or horizontally
- Pressure rating: 125 PSI at 75° F (24° C)
- Meets ASTM D2466 Standard
- Not for use with compressed air, gases or potable water

MLP79579



MLP79582



1 YEAR
LIMITED WARRANTY

Ball Valve / Check Valve /
Union Combination

PVC

TYPE 1



Application

One way check valve prevents backflow of water into sump pit. Ball valve allows for easy disassembly and service.

Dimensional Data

Model	MLP79582	MLP79579
IPS Pipe Size	1-1/2"	2"
Weight	1.6 lbs.	2.3 lbs.
A	3.12	3.40
B	4.88	4.88
C	5.05	6.08
D	8.00	9.25
E	3.94	4.59

Product Specifications

NO.	PART	MATERIAL	QTY
1	Upper Body	PVC	1
2	Valve Handle	Polyethylene	1
3	Ball Valve Seat	TPR	2
4	O-Ring	BUNA-N	1
5	Ball Valve	PVC	1
6	Valve Stem	PVC	1
7	Ball Valve Retaining Nut	PVC	1
8	O-Ring	BUNA-N	1
9	Connecting Nut	PVC	1
10	Lower Body	PVC	1
11	Flapper Disc	PVC	1
12	Flapper Seat	BUNA-N	1
13	O-Ring	BUNA-N	1
14	Union Nut	PVC	1
15	Union Socket	PVC	1

