

HORSEPOWER

MOTOR



6

Shallow Well Jet Pump

FEATURES

- 1-1/4" NPT suction •
- Built-in thermal overload protection for safety •
- Rugged cast iron pump body for durability •
- Glass reinforced thermoplastic impeller •
- Cast iron seal plate
- Pre-mounted, fully adjustable pressure switch •
- For shallow well application up to 25' depth •
- Maximum pressure: 74psi
- 1" NPT discharge
- Pressure switch pre-set to 20/40 PSI





MainlineCollection.com





MLP74705

RUGGED CAST IRO

Shallow Well Jet Pump





Application

Bringing potable water from a water source into the home.

Motor Specifications					
Horsepower	3/4 HP				
Voltage	115 / 230				
Amps	7.8/3.9				
Hertz	60 Hz				
Phase	Single				
Motor Type	Dual voltage TEFC (Totally enclosed fan cooled)				
Insulation	Class A				
Circuit Requirements	15 amp (min) individual circuit				
Duty Rating	Continuous				
Motor Shaft	Stainless Steel				
Motor Cooling	Air cooled				
Motor Protection	Auto reset thermal overload protector				
*For continuous operation, the	pump hosing must be filled to prevent the motor from overheating.				
Pump Specifications					
Discharge Size	1" NPT				
Suction Port Size	1-1/4" NPT				
Pump Housing	Cast iron				
Impeller Material	Glass reinforced thermoplastic				
Pressure switch	20/40				
Max Pressure	74 psi				
Max Flow Rate	13.75 gpm				
Liquid Temp. Range	32°- 120° F				
Warranty	3 Years				
Weight	33 lbs				

Performances

Approximate gallons per minute output at 40 psi							
Lift	0'	5′	10′	15′	20′	25′	
Gallons Per Minute	11.8	11.3	10.8	10.2	9.3	8.3	

Dimensions

