

12

HORSEPOWER

MOTOR



RUGGED CAST IRON Convertible Jet Pump

FEATURES

- 1-1/4" NPT suction •
- Built-in thermal overload protection for safety •
- Rugged cast iron pump body for durability •
- Glass reinforced thermoplastic impeller •
- Cast iron seal plate
- Pre-mounted, fully adjustable pressure switch •
- For shallow well application up to 25' depth •
- Can be used in deep well applications up to 80' depth •
- Maximum pressure: 58 psi •
- 1" NPT discharge and drive ports •
- Pressure switch pre-set to 20/40 PSI
- Ejector kit included





MainlineCollection.com





MLP74515

US

RUGGED CAST IRO

Convertible Jet Pump





Application

Bringing potable water from a water source into the home.

Motor Specifications								
Horsepower	1/2 HP							
Voltage	115 / 230							
Amps	6.4 / 3.2							
Hertz	60 Hz							
Phase	Single							
Motor Type	Dual voltage TEFC (Totally enclosed fan cooled)							
Insulation	Class A							
Circuit Requirements	15 amp (min) individual circuit							
Duty Rating	Continuous							
Motor Shaft	Stainless Steel							
Motor Cooling	Air cooled							
Motor Protection	Auto reset thermal overload protector							
*For continuous operation, the	pump hosing must be filled to prevent the motor from overheating.							
Pump Specification	5							
Discharge Size	1″ NPT							
Drive Port Size	1″ NPT							
Suction Port Size	1-1/4" NPT							
Pump Housing	Cast iron							
Impeller Material	Glass reinforced thermoplastic							
Pressure switch	20/40							
Max Pressure	58 psi							
Max Flow Rate	9.9 gpm							
Liquid Temp. Range	32°- 120° F							
Warranty	3 Years							
Weight	32.6 lbs							

Performances

Approximate gallons per minute output at 40 psi														
Lift	0'	5′	10′	15′	20′	25′	30'	40′	50'	60′	70'	80′		
Gallons Per Minute	7.0	6.2	5.8	5.1	4.5	3.8	3.3	2.0	0.8	-	-	-		

Dimensions



