Pneumatic Plugs

- Test-Ball ®
- Muni-Ball ®
- Pressure Charts
- Rupture Disc
- Protective Sleeves
- Remo®
- Big-Mouth® Flow-Through
- Factory-Replaceable Sleeve Muni-Ball®
- Jet-Ball®
- Air-Loc® Leak Locator
- Long Test-Ball® MS2 Test-Ball®
- Clean-Seal ®
- Pillow Plugs

Mechanical Plugs
Deflection Gauges
Testing Equipment
Tools&Accessories
Technical Data
Contact Us
Used Inventory
Search

Clean-Seal®

Designed for stack testing of drain, waste, and vent plumbing systems, Clean-Seal® plugs thread into a standard test tee. The bladder is inflated and then water is introduced into the pipe. Upon test completion, deflate the bladder; water travels down the pipe, eliminating test water backsplash.

Features:

- **Works in both plastic and cast-iron test tees**
- **Natural rubber body provides a leak-free seal**
- **High-impact ABS threads for maximum durability**
- **Removable/replaceable tire inflation valve fitting**

Clean-Seal® Application



Inflated (test)

Deflated (test release)





Simply thread into test tee and inflate (for maximum sealing performance, apply thread seal tape to the threads before use).

Part Number	Nominal Size	Maximum Back Pressure		Inflation Pressure	Product Weight	Deflated Length	Deflated Diameter	Inflation Thread
				Clean-Seal				
271508	1.5" (40 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	30 psi (2,1 bar)	.15 lbs (0.07 kg)	4.75" (121 mm)	1.5" (38 mm)	1/8"
271705	2" (50 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	.3 lbs (0.14 kg)	5.81" (150 mm)	2.38" (60 mm)	1/8"
271713	3" (75 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	.8 lbs (0.36 kg)	7.38" (188 mm)	3.5" (89 mm)	1/4"
271721	4" (100 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	35 psi (2,4 bar)	1.3 lbs (0.59 kg)	8.5" (215 mm)	4.5" (115 mm)	1/4"
271758	6" (150 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	25 psi (1,7 bar)	3.5 lbs (1.59 kg)	11" (280 mm)	6.63" (168 mm)	1/4"