



**SECTION 1 - IDENTIFICATION**

<p>Manufacturer:          Black Swan Mfg. Co.          4540 W. Thomas St.          Chicago, IL 60651-3318          Tel.: 800-252-5796          Fax: 773-227-3705          Web Site : <a href="http://www.blackswanmfg.com">www.blackswanmfg.com</a>          E-mail : <a href="mailto:info@blackswanmfg.com">info@blackswanmfg.com</a></p>	<p>For any Transportation or Medical Chemical Emergencies call:</p> <p style="text-align: center;"><b>INFOTRAC</b></p> <p style="text-align: center;">(800) 535-5053 <b>OR</b> (352) 323-3500</p> <p style="text-align: center;">24 hours per day - 7 days a week</p>
<p><b>Product Name: Stik-It Epoxy Putty</b></p>	<p><b>Recommended Use:</b> Plugging, sealing, mending and patching almost anything, including metals, wood, glass, concrete, ceramics and most plastics.</p>

**SECTION 2 – HAZARD(S) IDENTIFICATION**

<p><b>Labels</b></p>  <p><b>Irritant</b></p>	<p style="text-align: center;"><b>NFPA</b></p> <table style="width: 100%;"> <tr> <td style="width: 50%;"> <p><b>HEALTH HAZARD</b>            4 – Deadly            3 – Extreme Danger            2 – Hazardous            1 – Slight Hazardous            0 – Normal Material</p> </td> <td style="width: 50%;"> <p><b>FIRE HAZARD</b>            Flash Points            4 – Below 73°F            3 – Below 100°F            2 – Above 100°F, Not exceeding 200°F            1 – Above 200°F            0 – Will not burn</p> </td> </tr> </table>  <p><b>SPECIFIC HAZARD</b>          Oxidizer OX          Acid ACID          Alkali ALK          Corrosive COR          Use NO WATER          Radioactive</p>	<p><b>HEALTH HAZARD</b>            4 – Deadly            3 – Extreme Danger            2 – Hazardous            1 – Slight Hazardous            0 – Normal Material</p>	<p><b>FIRE HAZARD</b>            Flash Points            4 – Below 73°F            3 – Below 100°F            2 – Above 100°F, Not exceeding 200°F            1 – Above 200°F            0 – Will not burn</p>	<p style="text-align: center;"><b>GHS Classification</b></p> <table style="width: 100%;"> <tr> <td style="width: 50%;"> <p style="text-align: center;"><b>Health</b></p> <p>Acute Toxicity: Not Established            Skin Irritation: Cat. 2            Eye Irritation: Cat. 2B            Skin Sensitization: Cat. 1</p> </td> <td style="width: 50%;"> <p style="text-align: center;"><b>Environmental</b></p> <p>Acute Aquatic Toxicity: Not Established            Chronic Aquatic Toxicity: Not Established</p> </td> </tr> </table> <hr/> <p style="text-align: center;"><b>Physical</b> None</p>	<p style="text-align: center;"><b>Health</b></p> <p>Acute Toxicity: Not Established            Skin Irritation: Cat. 2            Eye Irritation: Cat. 2B            Skin Sensitization: Cat. 1</p>	<p style="text-align: center;"><b>Environmental</b></p> <p>Acute Aquatic Toxicity: Not Established            Chronic Aquatic Toxicity: Not Established</p>				
<p><b>HEALTH HAZARD</b>            4 – Deadly            3 – Extreme Danger            2 – Hazardous            1 – Slight Hazardous            0 – Normal Material</p>	<p><b>FIRE HAZARD</b>            Flash Points            4 – Below 73°F            3 – Below 100°F            2 – Above 100°F, Not exceeding 200°F            1 – Above 200°F            0 – Will not burn</p>									
<p style="text-align: center;"><b>Health</b></p> <p>Acute Toxicity: Not Established            Skin Irritation: Cat. 2            Eye Irritation: Cat. 2B            Skin Sensitization: Cat. 1</p>	<p style="text-align: center;"><b>Environmental</b></p> <p>Acute Aquatic Toxicity: Not Established            Chronic Aquatic Toxicity: Not Established</p>									
<p><b>Signal Word</b> Warning</p> <p><b>HMIS</b></p> <table style="width: 100%;"> <tr> <td style="background-color: #000080; color: white; padding: 2px;">HEALTH</td> <td style="text-align: center; padding: 2px;"><b>2</b></td> </tr> <tr> <td style="background-color: #FF0000; color: white; padding: 2px;">FLAMMABILITY</td> <td style="text-align: center; padding: 2px;"><b>1</b></td> </tr> <tr> <td style="background-color: #FFD700; padding: 2px;">REACTIVITY</td> <td style="text-align: center; padding: 2px;"><b>1</b></td> </tr> </table>	HEALTH	<b>2</b>	FLAMMABILITY	<b>1</b>	REACTIVITY	<b>1</b>	<table style="width: 100%;"> <tr> <td style="width: 50%;"> <p style="text-align: center;"><b>Hazardous Statements</b></p> <p>H315: Causes skin irritation            H317: May cause an allergic skin reaction            H320: Causes eye irritation</p> </td> <td style="width: 50%;"> <p style="text-align: center;"><b>Precautionary Statements</b></p> <p>P261: Avoid breathing dust            P264: Wash thoroughly after handling            P272: Contaminated work clothing should not be allowed out of the work place            P280: Wear protective gloves/protective clothing/eye protection/face protection</p> </td> </tr> </table>		<p style="text-align: center;"><b>Hazardous Statements</b></p> <p>H315: Causes skin irritation            H317: May cause an allergic skin reaction            H320: Causes eye irritation</p>	<p style="text-align: center;"><b>Precautionary Statements</b></p> <p>P261: Avoid breathing dust            P264: Wash thoroughly after handling            P272: Contaminated work clothing should not be allowed out of the work place            P280: Wear protective gloves/protective clothing/eye protection/face protection</p>
HEALTH	<b>2</b>									
FLAMMABILITY	<b>1</b>									
REACTIVITY	<b>1</b>									
<p style="text-align: center;"><b>Hazardous Statements</b></p> <p>H315: Causes skin irritation            H317: May cause an allergic skin reaction            H320: Causes eye irritation</p>	<p style="text-align: center;"><b>Precautionary Statements</b></p> <p>P261: Avoid breathing dust            P264: Wash thoroughly after handling            P272: Contaminated work clothing should not be allowed out of the work place            P280: Wear protective gloves/protective clothing/eye protection/face protection</p>									

**SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

<u>Chemicals</u>	<u>CAS#</u>	<u>EINECS#</u>	<u>REACH</u> <u>Pre-registration Number</u>	<u>Approx %</u>
BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN	25068-38-6	N/A	N/A	10-30%
2,4,6-TRIS (DIMETHYLAMINOMETHYL) PHENOL	90-72-7	N/A	N/A	1-5%
CRYSTALLINE SILICA NON-RESPIRABLE	14808-60-7	N/A	N/A	0.1-1%

\*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

**SECTION 4 – FIRST-AID MEASURES**

<p><b>Inhalation:</b> Move into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and call physician.  <b>Skin:</b> Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Wash skin thoroughly with soap and water. Get medical attention.  <b>Eyes:</b> Flush with water for 15 minutes. Remove contact lenses is present and easy to do so. If irritation persists, get medical attention.  <b>Ingestion:</b> Give 1 or 2 glasses of water. DO NOT INDUCE VOMITING. Contact physician immediately.</p>
--

# GHS SAFETY DATA SHEET

## SECTION 5 – FIRE-FIGHTING MEASURES

**Fire Hazard:** None.  
**Combustion Products:** None.  
**Extinguishing Media:** Carbon Dioxide Gas, Dry Chemical Powder.  
**Unsuitable Extinguishing Media:** Water, Foam.  
**Protective Equipment:** Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}. Full protective gear.  
**Special Fire Fighting Procedures:** Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers, to minimize risk of rupture. Do NOT enter confined fire space without full protective gear. If possible, contain fire run-off water.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.  
**Protective Equipment:** None.  
**Emergency Procedures:** None.  
**Environmental Precautions:** Avoid runoff into storm sewers, ditches and waterways.  
**Methods for Cleaning Up:** Absorb spill with inert material, then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area.

## SECTION 7 – HANDLING AND STORAGE

<u>Handling</u>	<u>Storage</u>
Use with adequate ventilation. Avoid breathing vapors, aerosol or mist. Provide appropriate ventilation/respiratory protection against decomposition products during welding/flame cutting operations and to protect against dust during sanding /grinding of cured product.	Store in a cool, dry, well-ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Hazardous Chemicals</u>	<u>Exposure Limits</u> <u>ACGIH-TLV</u>	<u>ACGIH-STEL</u>	<u>OSHA-PEL</u>
CRYSTALLINE SILICA NON-RESPIRABLE	TWA: 0.025 mg/m <sup>3</sup> - FORM: RESPIRABLE FRACTION	N/A	TWA: 10 mg/m <sup>3</sup> FORM: RESPIRABLE

**Engineering Controls:** Use appropriate engineering controls such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.  
**Ventilation:** Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment.  
**Personal Protective Equipment – Respiratory:** A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.  
**Personal Protective Equipment – Skin:** Wear appropriate protective gloves and other protective apparel to prevent skin contact.  
**Personal Protective Equipment – Eyes:** Wear appropriate protective glasses or splash goggles.

## SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

<b>Appearance:</b> Putty	<b>Flash Point:</b> >400°F (205.4°C)	<b>Vapor Pressure:</b> 0.03mm Hg @20°C
<b>Odor:</b> Slight	<b>Specific Gravity:</b> 1.19	<b>Flammability:</b> Not Established
<b>pH:</b> Not Established	<b>Solubility (H2O):</b> Negligible	<b>Flammability Limits:</b> LEL – Not Established
<b>Melting Point:</b> Not Established	<b>Evaporation Rate:</b> <<1	UEL – 11.8%
<b>Freezing Point:</b> Not Established	<b>Vapor Density:</b> >1	
<b>Boiling Point:</b> >500°F (260°C)	<b>VOC:</b> 0 g/l	

# GHS SAFETY DATA SHEET

## SECTION 10 – STABILITY AND REACTIVITY

**Stability:** Stable.

**Hazardous polymerization:** Will not occur.

**Conditions to avoid:** Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Heating resin above 300°F in the presence of air may cause slow oxidative decomposition.

**Incompatible materials:** Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (specially primary and secondary aliphatic amines).

**Hazardous decomposition products:** None known.

## SECTION 11 – TOXICOLOGICAL INFORMATION

<u>Hazardous Chemicals</u>	<u>Toxicity</u>	
	<u>LD<sub>50</sub></u>	<u>LC<sub>50</sub></u>
2,4,6-TRIS (DIMETHYLAMINOMETHYL) PHENOL	Dermal: 1280 mg/kg (rat) Oral: 1200 mg/kg (rat)	N/A N/A

**Likely Routes of Exposure:** Inhalation, Skin Contact, Eye Contact and Ingestion.

**Symptoms and Effect - Inhalation:** Respiratory tract irritation. High concentration may cause dizziness, headaches, and anesthetic effects. May cause respiratory sensitization with asthma-like symptoms.

**Skin Contact:** Can cause skin irritation; itching, redness, rashes, hives, burning and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction.

**Eye Contact:** Can cause moderate irritation, burning sensation, tearing, redness and swelling. Over exposure may cause lacrimation, corneal damage and permanent injury.

**Ingestion:** Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.

**Long-Term Effect:** Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction. Overexposure can cause headaches, dizziness, nausea and vomiting.

**Pre-Existing Conditions:** Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

## SECTION 12 – ECOLOGICAL INFORMATION

**Ecotoxicity:** None known.

**Persistence & Degradability:** None known.

**Bioaccumulative Potential:** None known.

**Mobility in soil:** None known.

## SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

## SECTION 14 – TRANSPORTATION INFORMATION

D.O.T. (U.S.): Not Regulated.

## SECTION 15 – REGULATORY INFORMATION

**Precautionary Label Information:** None.

**Risk Phrases:** None.

**Safety Phrases:** S2-Keep out of reach of children.

## SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2015