

PTFE Thread Seal Tape

Product Specifications



ML15080



ML15100

Description

Mainline PTFE Thread Seal Tape is a clean, self-lubricating tape, which is used to make threaded connections. It offers a positive pressure seal to 10,000 lbs. PSI from a temperature range from -450° F to +500° F. Thickness is .0035 ± .0005. PTFE Thread Seal Tape is non-toxic and non-flammable.

Meets Federal Specification MIL-T-27730A.

Directions for Use

- Apply PTFE Thread Seal Tape to male threads as close as possible to end of threads. Hold end of PTFE Thread Seal Tape firmly and wind clockwise on standard threads. Stretch tape tightly as you wind.
- Continue to wind and stretch tape so the tape seats into threads. Wind once around on joints under 2" and twice around on larger sizes.
- Complete winding and overlap starting point about 1". Tear tape by pulling in same direction as you were winding. Smooth torn end by running fingers over it.
- Assemble joints in usual manner.

✓ To Submit	Part No.	Size
	ML15075	1/2" X 520"
	ML15080	1/2" X 260"
	ML15085	3/4" X 520"
	ML15090	3/4" X 260"
	ML15095	1" X 520"
	ML15100	1/2" X 260" YELLOW-GAS

MSDS

See MSDS sheet for more details.

Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.

Contact your sales representative for more information or visit our website at mainlinecollection.com