Heavy Duty Import No-Hub Couplings

Product Specifications



Product Features:

- Engineered to connect no-hub cast iron pipe, replacing less efficient hub and spigot material
- All bands, housings, screws and shields constructed using stainless steel
- UPC and IPC Approved
- ISO 9001:2000



Material & Specifications:

- Complete: Conforms to FM 1680, ASTM C1540
- Clamp: Type 310 stainless steel
- Screw: Type 305 stainless steel, 3/8" hex head/shoulder
- Shield: Type 310 stainless steel, patterned, bright annealed, thickness 0.009"
- Gasket: Neoprene (ASTM C564)

✓ To Submit	Part #	Description	Installation Torque (in - Ibs)	# of Clamps for Coupling
	ML112HDNHC	1-1/2" Heavy Duty No-Hub Coupling – Import	80 - 100	4
	ML2HDNHC	2" Heavy Duty No-Hub Coupling – Import	80 - 100	4
	ML3HDNHC	3" Heavy Duty No-Hub Coupling – Import	80 - 100	4
	ML4HDNHC	4" Heavy Duty No-Hub Coupling - Import	80 - 100	4
	ML5HDNHC	5" Heavy Duty No-Hub Coupling – Import	80 - 100	6
	ML6HDNHC	6" Heavy Duty No-Hub Coupling - Import	80 - 100	6
	ML8HDNHC	8" Heavy Duty No-Hub Coupling – Import	80 - 100	6
	ML10HDNHC	10" Heavy Duty No-Hub Coupling – Import	80 - 100	6
	ML12HDNHC	12" Heavy Duty No-Hub Coupling – Import	80 - 100	6

Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.

Contact your sales representative for more information or visit our website at mainlinecollection.com