Flexible Repair Couplings

Product Specifications

MAINLINE

PRODUCT FEATURES

- Sizes 2" to 10"
- Connect to virtually any size pipe, quickly and easily
- Shear ring provides extra strength
- Leak-proof, shear and chemical resistant connection that is impervious to roots and unaffected by soil conditions
- Stainless Steel clamps are rust proof and corrosion resistant

MATERIALS

- Flexible elastomeric connectors
- Meets requirements of ASTM C1173 and CSA B602
- Stainless Steel shear ring and clamps
 - Shear Ring AISI Type 301 Stainless Steel
 - o Band AISI Type 301 Stainless Steel
 - Housing AISI Type 301 Stainless Steel
 - o Screw AISI Type 305 Stainless Steel 5/16" Slotted Hex Head
- Install to 60 inch-lbs. torque
- Pressure rated to maximum 4.3 PSI



✓ To Submit	Part #	Description	Note
	ML01-44RC	4" Clay x 4" Clay	
	ML01-64RC	6" Clay x 4" Clay	
	ML01-66RC	6" Clay x 6" Clay	
	ML01-88RC	8" Clay x 8" Clay	†
	ML01-1010RC	10" Clay x 10" Clay	†‡
	ML02-44RC	4" Clay x 4" Cast Iron, Plastic	
	ML02-64RC	6" Clay x 4" Cast Iron, Plastic	
	ML02-66RC	6" Clay x 6" Cast Iron, Plastic	
	ML02-88RC	8" Clay x 8" Cast Iron, Plastic	†
	ML02-1010RC	10" Clay x 10" Cast Iron, Plastic	†‡

ML56-22RC 2" Cast Iron, Plastic x 2" Cast Iron, Plastic *‡	
ML56-33RC 3" Cast Iron, Plastic x 3" Cast Iron, Plastic *‡	
ML56-44RC 4" Cast Iron, Plastic x 4" Cast Iron, Plastic *‡	
ML56-64RC 6" Cast Iron, Plastic x 4" Cast Iron, Plastic	
ML56-66RC 6" Cast Iron, Plastic x 6" Cast Iron, Plastic	
ML56-88RC 8" Cast Iron, Plastic x 8" Cast Iron, Plastic	
ML56-1010RC 10" Cast Iron, Plastic x 10" Cast Iron, Plastic ‡	

Notes, when indicated above:

- † This product not UPC certified
- ‡ This product not CSA certified
- This product not manufactured and assembled in the USA

Warranty

See warranty information for more details.





All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.