
Bugle Phillips Coarse Thread Drywall Screw Black


Product Specifications




PRODUCT FEATURES

· Black Phosphate Finish







| | Screw | Threads | Driver | | | A Head Diameter | | H Head Thickness | | R Recess Diameter | | I Recess Depth | | |
|----------------|-------------------------------|---|--------|--------------------|------------------|--------------------|------|---------------------|------|----------------------|------|-------------------|------|--|
| | Size | Per Inch | Size | Min. Diameter | Max Diameter | Min | Max | Min | Max | Min | Max | Min | Max | |
| | 6 | 8 | 2 | .142 | .154 | .315 | .347 | .020 | .031 | .176 | .189 | .087 | .110 | |
| | 7 | 8 | 2 | .159 | .172 | .322 | .355 | .020 | .035 | .191 | .206 | .102 | .125 | |
| | 8 | 8 | 2 | .163 | .180 | .330 | .363 | .020 | .039 | .201 | .214 | .112 | .135 | |
| | 10 | 8 | 2 | .180 | .210 | .344 | .379 | .020 | .045 | .208 | .222 | .137 | .142 | |
| | Tolerance on Length | | | Up to 1" 0, +0.060 | Over 1" 0,+0.100 | | | | | | | | | |
| Material | AISI 1018 or Equivalent Steel | | | | | | | | | | | | | |
| Hardness | Rockwell C44 minimum | | | | | | | | | | | | | |
| Heat Treatment | | Quenched in liquid and then tempered by reheating to 650° Minimum | | | | | | | | | | | | |

Warranty: See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.