

Tub & Tile Siliconized Acrylic Latex Caulk

Product Specifications

Page 1 of 2



MAINLINE TUB & TILE CAULK is a premium quality, siliconized acrylic caulk. Properties include outdoor weathering, minimum shrinkage, long tooling time and much more. It is resistance to oxidation and ultra-violet rays. The siliconized feature improves the adhesion to ceramic and glass substrates. Provides a waterproof & weatherproof seal without the use of a primer. It can be painted with latex or oil-based paints.

- Paintable and easy clean up
- Exterior and Interior Use
- Mildew Resistant
- Non-Staining, Non-Yellowing
- Long Life Expectancy
- Meets ASTM C-834-76 Specifications

Packaging	Color	Model #
5.5 fl oz. (162 mL)	Clear	ML01085
5.5 fl oz. (162 mL)	White	ML01075
10.3 fl oz. (304 mL)	White	ML01077

SUGGESTED USES:

- Aluminum
- Concrete
- Glass
- Areas with high moisture
- Wood
- Brick
- Ceramic Tiles

LIMITATIONS:

- Cannot be used for joints immersed in water or subjected to high abrasion below 40°
- Protect the product from freezing
- Do not expose to water or rain for at least 24 hours
- Store in a cool, dry place at room temperature. Protect from freezing

SAFETY

See Safety Data Sheet (SDS) for safety information or product label. Do not ingest. If swallowed do not induce vomiting. If smeared into eyes, flush with water for 15 minutes. Call physician. Keep out of reach of children.

Warranty: See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.



Contact your sales representative for more information or visit our website at mainlinecollection.com

Tub & Tile Siliconized Acrylic Latex Sealant

Product Specifications

Page 2 of 2



APPLICATION:

- Surface must be clean and free of dust, oil and other foreign substances.
- Cut nozzle on cartridge or tip on tube to desired bead size of 1/4" to 3/8".
- Apply at temperatures above 40°F. For best results remove all of the old caulking before applying.
- Tool within 30 minutes with wet fingers or damp smooth sponge.
- It can be painted over after 2 hours with oil or latex based paints.
- Excess caulk and tools can be cleaned easily with soap and water.

TECHNICAL DATA	
Type	Acrylic Latex
Solids By Weight	85%
Specific Gravity	1.55 G/CC
Slump at Rt	0.02" (NEGLIGIBLE)
Shore At Hardness	25
Application Temperature	40° F to 100° F
Service Temperature	-5° F to 170° F
Tooling Time	30 min at RT 50% RH
Cure Time	1 week
Elongation At Break	350%
Modulus At 100% E	95 PSI
Movement Capability	10%

Warranty: See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.



Contact your sales representative for more information or visit our website at mainlinecollection.com