Push Connect® Brass Reducing Couplings

Product Specifications

Page 1 of 2



PRODUCT FEATURES

- Forged Lead Free* Brass
- Maximum Working Pressure: 200 PSI
- Maximum Temperature Rating: 200° F
- Compatible with Copper, CPVC, PEX & PE-RT
- Replaceable O-Ring Seal Design
- Removable and Reusable
- Push to Connect
- Full Flow
- Available with Pre-Inserted Stiffener
- Dual Seal on Sizes 1-1/4" and Larger

APPROVED APPLICATIONS

- Plumbing
- · Hydronic Heating
- Heating
- Behind Walls without
- Irrigation
- Access Panel
- Underground

NOTE: When using PEX, a tube stiffener should be inserted into the PEX tubing end prior to insertion into the fitting.

√To Submit	Part #	Size		
	MLU009LF	1/2" x 3/8"		
	MLU8408LF	3/8" x ½"		
	MLU058LF	3/4" x 1/2"		
	MLU060LF	1" x 3/4"		
	MLU009LF-S	1/2" x 3/8" w/ Stiffener		
	MLU8408LF-S	3/8 x 1/4" w/Stiffener		
	MLU058LF-S	3/4" x 1/2" w/ Stiffener		
	MLU060LF-S	1" x 3/4" w/ Stiffener		



FORCES FOR MECHANICAL SEPARATION TEST

Nominal Size		Longitudinal (Pull) Test		
Inches	mm	Lbf	N	
3/8 or <	10 or <	100	444.8	
1/2	13	150	667	
3/4	19	275	1223.2	
1	25	475	2112.8	

Warranty

See warranty information for more details.







All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.

Push Connect® Brass Reducing Couplings


Product Specifications

Page 2 of 2



MATERIALS & SPECIFICATIONS

#	Component	Material			
		< = 1"	> 1"		
1	Body	Lead Free Brass	Lead Free Brass		
2	Seat Ring	POM	Lead Free Brass		
3	Push Ring	POM	Lead Free Brass		
4	Grip ring	Stainless Steel	Stainless Steel		
5	O-Ring Seal	EPDM70	EPDM70		



DIMENSIONS

#	Øa	Øb	Da	Db	L
MLU009LF	0.64	0.515	1	81	1.88
MLU8408LF	TBD	TBD	TBD	TBD	TBD
MLU058LF	0.88	0.64	1.06	1	2.38
MLU060LF	1.142	0.88	1.31	1.06	2.47
MLU009LF-S	0.64	0.515	1	81	1.88
MLU8408LF-S	TBD	TBD	TBD	TBD	TBD
MLU058LF-S	0.88	0.64	1.06	1	2.38
MLU060LF-S	1.142	0.88	1.31	1.06	2.47

