## Push Connect® Brass 90 Degree Elbows

**Product Specifications** 

Page 1 of 2



## **PRODUCT FEATURES**

- Forged Lead Free\* Brass
- Maximum Working Pressure: 200 PSI
- Maximum Temperature Rating: 200° F
- Compatible with Copper, CPVC, PEX & PE-RT
- Replaceable O-Ring Seal Design
- Removable and Reusable
- Push to Connect
- Full Flow
- Available with Pre-Inserted Stiffener
- Dual Seal on Sizes 1-1/4" and Larger

#### **APPROVED APPLICATIONS**

- Plumbing
- · Hydronic Heating
- Heating
- Behind Walls without
- Irrigation
- Access Panel
- Underground

NOTE: When using PEX, a tube stiffener should be inserted into the PEX tubing end prior to insertion into the fitting.

√To Submit	Part #	Size
	MLU244LF	1/4" x 1/4"
	MLU246LF	3/8" x 3/8"
	MLU248LF	1/2" x 1/2"
	MLU256LF	3/4" x 3/4"
	MLU260LF	1" x 1"
	MLU246LF-S	3/8" x 3/8" w/ Stiffener
	MLU248LF-S	1/2" x 1/2" w/ Stiffener
	MLU256LF-S	3/4" x 3/4" w/ Stiffener
	MLU260LF-S	1" x 1" w/ Stiffener



#### FORCES FOR MECHANICAL SEPARATION TEST

Nominal Size		Longitudinal (Pull) Test	
Inches	mm	Lbf	N
3/8 or <	10 or <	100	444.8
1/2	13	150	667
3/4	19	275	1223.2
1	25	475	2112.8

## Warranty

See warranty information for more details. All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.











# Push Connect® Brass 90 Degree Elbows


**Product Specifications** 

Page 2 of 2



## **MATERIALS & SPECIFICATIONS**

#	Component	Material		
		< = 1"	> 1"	
1	Body	Lead Free Brass	Lead Free Brass	
2	Seat Ring	POM	Lead Free Brass	
3	Push Ring	POM	Lead Free Brass	
4	Grip ring	Stainless Steel	Stainless Steel	
5	O-Ring Seal	EPDM70	EPDM70	



#### **DIMENSIONS**

#	Ø	D	L
MLU244LF	TBD	TBD	TBD
MLU246LF	0.515	0.81	1.58
MLU248LF	0.64	1	1.86
MLU256LF	0.88	1.06	1.87
MLU260LF	1.142	1.31	2.8
MLU246LF-S	0.515	0.81	1.58
MLU248LF-S	0.64	1	1.86
MLU256LF-S	0.88	1.06	1.87
MLU260LF-S	1.142	1.31	2.8

