

Epoxy Putty

Product Specifications



Description

Mainline Epoxy Putty is a hand kneadable fast curing epoxy putty that mixes in one minute to provide permanent repairs to many surfaces including metals, wood, glass, concrete, ceramics and numerous plastics. One hour after mixing, Epoxy Putty can be drilled, sawed, sanded, filed, tapped, machined or painted. Epoxy Putty is a general purpose epoxy putty.

Directions for Use

- Break off required portion of material.
- Twist and knead until uniform color is achieved - no streaks
- Apply at once to surface (2 minute work life).
- Remove excess before it hardens.

✓ To Submit	Part No.	Description
	ML15020	Epoxy Putty

Application Properties	Results
Working Life:	2 Minutes
Shelf Stability:	12 Months Minimum @ 75° F
Shored Hardness (Shore D) (Full Cure, 24 Hours):	80
Lap Shear Tensile Strength On Steel (1" x 1" x 1/16" lbs.):	900
Temperature Limitations:	250° F Continuous, 300° F Intermittent
Chemical Resistance:	Resistant To Hydrocarbons, Ketones, Alcohol, Esters
Electrical Resistance:	30,000 Megohms
Dielectric Strength:	300 Volts/Mil
Shrinkage:	Less Than 1%
Non-volatile I content:	100%
Compressive strength:	12,000 PSI

CAUTION

Contains epoxy resins and amine which may cause irritation to sensitive skin. Wash hands with soap and water after use. Eye irritant. In case of eye contact, flush with water. Contact physician. May be harmful if swallowed. Keep out of reach of children.

MSDS

See MSDS sheet for more details.

Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.



Contact your sales representative for more information or visit our website at mainlinecollection.com