

- Thermostats
 - > Programmable Thermostats
 - > Non-Programmable Thermostats
 - > Thermostat Parts and Accessories
- Whole House Air Quality
- HVAC Zoning
- Residential Combustion
 - EnviraCOM
 - Communications
 - Water Control
 - Training Materials & Product Literature

- Quick Links**
- Tradeline Catalog Printed Version (114 MB)
 - Tradeline Catalog CD-ROM version (50 MB)

- Locators**
- ACI Contractor
 - Residential Contractor
 - Distributor

Environmental & Combustion Controls



> Programmable Thermostats > Digital System Accessories > C7089

C7089U1006

C7089 Remote Outdoor Sensor

- [Locate Distributors](#)
- [Product Specifications](#)
- [Literature and Documents](#)



Overview

Remote outdoor temperature sensor, when installed, the current outdoor temperature is displayed. Also can be used to manage dual fuel and lock-out expensive auxiliary heat in heat pump applications.

Features

- Convenience feature for homeowners.
- Mounting clip allows easy sensor positioning on siding or soffit.
- Includes 60 in. leadwires.
- Factory calibrated; no field calibration required.
- Maximum wire run of 200 feet.

Product Specifications [→ Back To Top](#)

Description	Outdoor Sensor used to measure the outdoor temperature for use with VisionPro and VisionPRO IAQ
Application	Sensor for VisionPRO Thermostats
Application	Outdoor sensor for VisionPRO and VisionPRO IAQ Thermostats
Dimensions (in.)	2 1/4 in. x 3/8 in. with 60 in. leadwires.
Dimensions (mm)	57 mm x 10 mm with 1524 mm leadwires.
Mounting	Mounting Clip provided and screws provided.
Operating Humidity Range (% RH)	5 to 95% RH, non-condensing
Temperature Range, Ambient (F)	-40 F to +120 F

Welcome

[Login to My Account](#) →

[→ New User Registration](#)

[→ Find Quote](#)

Product Search

→

Cross Reference Search

→

Search

→

[→ Advanced Search](#)

Literature / Image Search

All Literature ▼

Model / Part Number ▼

→